



GIOVENZANA

INTERNATIONAL B.V.



LIFT




GM442N

IP65

DESCRIPTION

Emergency stop
EN ISO 13850
Ø 40 twist to release with:




1 Up push button - 2NO



1 Down push button - 2NO



1 Cam switch 1-O-2
90° switching - 2NO + 2NC



SCHEME

CAM SWITCHES

Rated operating voltage U_e [V]: 690
Rated insulation voltage U_i [V]: 690
Rated impulse withstand voltage U_{imp} [kV]: 4
Rated thermal current I_{th} [A]: 20
Rated thermal current in enclosure I_{the} [A]: 16
Frequency [Hz]: 50/60

CONTACT BLOCKS

Rated operating voltage U_e [V]: 690
Rated insulation voltage U_i [V]: 690
Rated impulse withstand voltage U_{imp} [kV]: 4
Rated thermal current I_{th} [A]: 16
Rated thermal current I_{the} [A]: 16
Frequency [Hz]: 50/60
Rated operating current: AC 15 – DC 13




GM444N

IP65

DESCRIPTION

Emergency stop
EN ISO 13850
Ø 40 twist to release with:




1 Up push button - 2NO



1 Down push button - 2NO



1 Cam switch 1-2
90° switching - 2NO + 2NC



SCHEME

CAM SWITCHES

Rated operating voltage U_e [V]: 690
Rated insulation voltage U_i [V]: 690
Rated impulse withstand voltage U_{imp} [kV]: 4
Rated thermal current I_{th} [A]: 20
Rated thermal current in enclosure I_{the} [A]: 16
Frequency [Hz]: 50/60

CONTACT BLOCKS

Rated operating voltage U_e [V]: 690
Rated insulation voltage U_i [V]: 690
Rated impulse withstand voltage U_{imp} [kV]: 4
Rated thermal current I_{th} [A]: 16
Rated thermal current I_{the} [A]: 16
Frequency [Hz]: 50/60
Rated operating current: AC 15 – DC 13





PIT BOTTOM, RECALL DRIVE CONTROL UNITS AND CAR TOP INSPECTION BOXES - GM Series



GM441N

IP54

DESCRIPTION	SCHEME
Emergency stop EN ISO 13850 Ø 40 twist to release with:	
1 Up push button - 2NO	
1 Down push button - 2NO	
1 Cam switch 1-2 90° switching - 2NO + 2NC	
1 Schuko socket outlet 16A	
1 Cenelec socket outlet	
1 USA socket outlet	
1 Swiss socket outlet	
1 UK standard socket outlet	
1 Australia-China socket outlet	

CAM SWITCHES

Rated operating voltage U_e [V]: 690
Rated insulation voltage U_i [V]: 690
Rated impulse withstand voltage U_{imp} [kV]: 4
Rated thermal current I_{th} [A]: 20
Rated thermal current in enclosure I_{the} [A]: 16
Frequency [Hz]: 50/60

CONTACT BLOCKS

Rated operating voltage U_e [V]: 690
Rated insulation voltage U_i [V]: 690
Rated impulse withstand voltage U_{imp} [kV]: 4
Rated thermal current I_{th} [A]: 16
Rated thermal current I_{the} [A]: 16
Frequency [Hz]: 50/60
Rated operating current: AC 15 – DC 13

GM441N/FR

GM441N/US

GM441N/SW

GM441N/UK

GM441N/CH



GM445N

IP54

DESCRIPTION	SCHEME
Emergency stop EN ISO 13850 Ø 40 twist to release with:	
1 Up push button - 2NO	
1 Down push button - 2NO	
1 Cam switch 1-0-2 90° switching - 2NO + 2NC	
1 Schuko socket outlet 16A	
1 Cenelec socket outlet	
1 USA socket outlet	
1 Swiss socket outlet	
1 UK standard socket outlet	
1 Australia-China socket outlet	

CAM SWITCHES

Rated operating voltage U_e [V]: 690
Rated insulation voltage U_i [V]: 690
Rated impulse withstand voltage U_{imp} [kV]: 4
Rated thermal current I_{th} [A]: 20
Rated thermal current in enclosure I_{the} [A]: 16
Frequency [Hz]: 50/60

CONTACT BLOCKS

Rated operating voltage U_e [V]: 690
Rated insulation voltage U_i [V]: 690
Rated impulse withstand voltage U_{imp} [kV]: 4
Rated thermal current I_{th} [A]: 16
Rated thermal current I_{the} [A]: 16
Frequency [Hz]: 50/60
Rated operating current: AC 15 – DC 13

GM445N/FR

GM445N/US


GM445N/SW

GM445N/UK

GM445N/CH

GM660

IP54  Magnets on the bottom by request

DESCRIPTION	SCHEME
Emergency stop EN ISO 13850 Ø 40 twist to release with:	
1 Up push button - 2NO	 
1 Down push button - 2NO	 
1 Alarm push button 1NO + 1NC	 
1 Cam switch 1-2 90° switching - 3NO + 3NC	
1 Schuko socket outlet 16A	
1 Cenelec socket outlet	
1 USA socket outlet	
1 Swiss socket outlet	
1 UK standard socket outlet	
1 Australia-China socket outlet	

CAM SWITCHES

Rated operating voltage U_e [V]: 690
 Rated insulation voltage U_i [V]: 690
 Rated impulse withstand voltage U_{imp} [kV]: 4
 Rated thermal current I_{th} [A]: 20
 Rated thermal current in enclosure I_{the} [A]: 16
 Frequency [Hz]: 50/60

CONTACT BLOCKS

Rated operating voltage U_e [V]: 690
 Rated insulation voltage U_i [V]: 690
 Rated impulse withstand voltage U_{imp} [kV]: 4
 Rated thermal current I_{th} [A]: 16
 Rated thermal current I_{the} [A]: 16
 Frequency [Hz]: 50/60
 Rated operating current: AC 15 – DC 13

GM660/FR

GM660/US

GM660/SW


GM660/UK

GM660/CH



GM663

IP54  Magnets on the bottom by request

DESCRIPTION	SCHEME
Emergency stop EN ISO 13850 Ø 40 push-pull with:	
1 Up push button - 2NO	 
1 Down push button - 2NO	 
1 Common push button - 2NO	 
1 Cam switch 1-2 90° switching - 3NO + 3NC	
1 Schuko socket outlet 16A	
1 Cenelec socket outlet	
1 USA socket outlet	
1 Swiss socket outlet	
1 UK standard socket outlet	
1 Australia-China socket outlet	

CAM SWITCHES

Rated operating voltage U_e [V]: 690
 Rated insulation voltage U_i [V]: 690
 Rated impulse withstand voltage U_{imp} [kV]: 4
 Rated thermal current I_{th} [A]: 20
 Rated thermal current in enclosure I_{the} [A]: 16
 Frequency [Hz]: 50/60

CONTACT BLOCKS

Rated operating voltage U_e [V]: 690
 Rated insulation voltage U_i [V]: 690
 Rated impulse withstand voltage U_{imp} [kV]: 4
 Rated thermal current I_{th} [A]: 16
 Rated thermal current I_{the} [A]: 16
 Frequency [Hz]: 50/60
 Rated operating current: AC 15 – DC 13

GM663/FR

GM663/US

GM663/SW

GM663/UK

GM663/CH





PIT BOTTOM, RECALL DRIVE CONTROL UNITS AND CAR TOP INSPECTION BOXES - GM Series



GM670

IP54 Magnets on the bottom by request

DESCRIPTION	SCHEME
Emergency stop EN ISO 13850 Ø 40 twist to release with:	
1 Up push button - 2NO	
1 Down push button - 2NO	
1 Alarm push button 1NO+1NC	
1 Cam switch 1-O-2 90° switching - 2NO + 2NC	
1 Schuko socket outlet 16A	
1 Cenelec socket outlet	
1 USA socket outlet	
1 Swiss socket outlet	
1 UK standard socket outlet	
1 Australia-China socket outlet	

CAM SWITCHES

Rated operating voltage U_e [V]: 690
Rated insulation voltage U_i [V]: 690
Rated impulse withstand voltage U_{imp} [kV]: 4
Rated thermal current I_{th} [A]: 20
Rated thermal current in enclosure I_{the} [A]: 16
Frequency [Hz]: 50/60

CONTACT BLOCKS

Rated operating voltage U_e [V]: 690
Rated insulation voltage U_i [V]: 690
Rated impulse withstand voltage U_{imp} [kV]: 4
Rated thermal current I_{th} [A]: 16
Rated thermal current I_{the} [A]: 16
Frequency [Hz]: 50/60
Rated operating current: AC 15 – DC 13

GM670/FR

GM670/US

GM670/SW

GM670/UK

GM670/CH



GM677

IP54 Magnets on the bottom by request

DESCRIPTION	SCHEME
Emergency stop EN ISO 13850 Ø 40 push-pull with:	
1 Up push button - 2NO	
1 Down push button - 2NO	
1 Common push button - 2NO	
1 Cam switch 1-O-2 90° switching - 3NO + 3NC	
1 Schuko socket outlet 16A	
1 Cenelec socket outlet	
1 USA socket outlet	
1 Swiss socket outlet	
1 UK standard socket outlet	
1 Australia-China socket outlet	

CAM SWITCHES

Rated operating voltage U_e [V]: 690
Rated insulation voltage U_i [V]: 690
Rated impulse withstand voltage U_{imp} [kV]: 4
Rated thermal current I_{th} [A]: 20
Rated thermal current in enclosure I_{the} [A]: 16
Frequency [Hz]: 50/60

CONTACT BLOCKS

Rated operating voltage U_e [V]: 690
Rated insulation voltage U_i [V]: 690
Rated impulse withstand voltage U_{imp} [kV]: 4
Rated thermal current I_{th} [A]: 16
Rated thermal current I_{the} [A]: 16
Frequency [Hz]: 50/60
Rated operating current: AC 15 – DC 13

GM677/FR

GM677/US

GM677/SW

GM677/UK

GM677/CH

GM750

IP54 ☐ Magnets on the bottom by request

DESCRIPTION	SCHEME
Emergency stop EN ISO 13850 Ø 40 push-pull with:	
1 Up push button - 2NO	
1 Down push button - 2NO	
1 Alarm push button - 1NO	
1 Common push button - 1NO	
1 Cam switch 1-2 90° switching - 2NO + 2NC	
1 Schuko socket outlet 16A	
1 Cenelec socket outlet	
1 USA socket outlet	
1 Swiss socket outlet	
1 UK standard socket outlet	
1 Australia-China socket outlet	

CAM SWITCHES

Rated operating voltage U_e [V]: 690
 Rated insulation voltage U_i [V]: 690
 Rated impulse withstand voltage U_{imp} [kV]: 4
 Rated thermal current I_{th} [A]: 20
 Rated thermal current in enclosure I_{the} [A]: 16
 Frequency [Hz]: 50/60

CONTACT BLOCKS

Rated operating voltage U_e [V]: 690
 Rated insulation voltage U_i [V]: 690
 Rated impulse withstand voltage U_{imp} [kV]: 4
 Rated thermal current I_{th} [A]: 16
 Rated thermal current I_{the} [A]: 16
 Frequency [Hz]: 50/60
 Rated operating current: AC 15 – DC 13

GM750/FR

GM750/US

GM750/SW

GM750/UK

GM750/CH



GM757

IP54 ☐ Magnets on the bottom by request

DESCRIPTION	SCHEME
Emergency stop EN ISO 13850 Ø 40 push-pull with:	
1 Up push button - 2NO - 1NC	
1 Down push button - 2NO - 1NC	
1 Knob selector 1-O-2 - 1NO+1NC	
1 Common push button - 2NO	
1 Cam switch 1-2 90° switching - 2NO + 2NC	
1 Schuko socket outlet 16A	
1 Cenelec socket outlet	
1 USA socket outlet	
1 Swiss socket outlet	
1 UK standard socket outlet	
1 Australia-China socket outlet	

CAM SWITCHES

Rated operating voltage U_e [V]: 690
 Rated insulation voltage U_i [V]: 690
 Rated impulse withstand voltage U_{imp} [kV]: 4
 Rated thermal current I_{th} [A]: 20
 Rated thermal current in enclosure I_{the} [A]: 16
 Frequency [Hz]: 50/60

CONTACT BLOCKS

Rated operating voltage U_e [V]: 690
 Rated insulation voltage U_i [V]: 690
 Rated impulse withstand voltage U_{imp} [kV]: 4
 Rated thermal current I_{th} [A]: 16
 Rated thermal current I_{the} [A]: 16
 Frequency [Hz]: 50/60
 Rated operating current: AC 15 – DC 13

GM757/FR

GM757/US

GM757/SW

GM757/UK

GM757/CH





PIT BOTTOM, RECALL DRIVE CONTROL UNITS AND CAR TOP INSPECTION BOXES - GM Series



GM758

IP54 Magnets on the bottom by request

DESCRIPTION	SCHEME
Emergency stop EN ISO 13850 Ø 40 push-pull with:	
1 Up push button - 2NO - 1NC	
1 Down push button - 2NO - 1NC	
1 Led light	
1 Common push button - 2NO	
1 Cam switch 1-2 90° switching - 2NO + 2NC	
1 Schuko socket outlet 16A	
1 Cenelec socket outlet	
1 USA socket outlet	
1 Swiss socket outlet	
1 UK standard socket outlet	
1 Australia-China socket outlet	

CAM SWITCHES

Rated operating voltage U_e [V]: 690
Rated insulation voltage U_i [V]: 690
Rated impulse withstand voltage U_{imp} [kV]: 4
Rated thermal current I_{th} [A]: 20
Rated thermal current in enclosure I_{the} [A]: 16
Frequency [Hz]: 50/60

CONTACT BLOCKS

Rated operating voltage U_e [V]: 690
Rated insulation voltage U_i [V]: 690
Rated impulse withstand voltage U_{imp} [kV]: 4
Rated thermal current I_{th} [A]: 16
Rated thermal current I_{the} [A]: 16
Frequency [Hz]: 50/60
Rated operating current: AC 15 – DC 13

GM758/FR

GM758/US

GM758/SW

GM758/UK

GM758/CH



GM751

IP65 Magnets on the bottom by request

DESCRIPTION	SCHEME
Emergency stop EN ISO 13850 Ø 40 push-pull with:	
1 Up push button - 2NO	
1 Down push button - 2NO	
1 Alarm push button - 1NO	
1 Common push button - 1NO	
1 Cam switch 1-2 90° switching - 2NO + 2NC	

CAM SWITCHES



Rated operating voltage U_e [V]: 690
Rated insulation voltage U_i [V]: 690
Rated impulse withstand voltage U_{imp} [kV]: 4
Rated thermal current I_{th} [A]: 20
Rated thermal current in enclosure I_{the} [A]: 16
Frequency [Hz]: 50/60

CONTACT BLOCKS

Rated operating voltage U_e [V]: 690
Rated insulation voltage U_i [V]: 690
Rated impulse withstand voltage U_{imp} [kV]: 4
Rated thermal current I_{th} [A]: 16
Rated thermal current I_{the} [A]: 16
Frequency [Hz]: 50/60
Rated operating current: AC 15 – DC 13

GM756

IP54  Magnets on the bottom by request

DESCRIPTION	SCHEME
Emergency stop EN ISO 13850 Ø 40 push-pull with:	
1 Up push button - 2NO - 1NC 	
1 Down push button - 2NO - 1NC 	
1 Alarm push button - 1NO 	
1 Common push button - 2NO 	
1 Cam switch 1-2 90° switching - 2NO + 2NC	
1 Red led light	 AC/DC 24V
1 Knob selector 1-O-2 1NO+1NO 	
1 Schuko socket outlet 16A	
1 Cenelec socket outlet	
1 USA socket outlet	
1 Swiss socket outlet	
1 UK standard socket outlet	
1 Australia-China socket outlet	

CAM SWITCHES

Rated operating voltage U_e [V]: 690
 Rated insulation voltage U_i [V]: 690
 Rated impulse withstand voltage U_{imp} [kV]: 4
 Rated thermal current I_{th} [A]: 20
 Rated thermal current in enclosure I_{the} [A]: 16
 Frequency [Hz]: 50/60

CONTACT BLOCKS

Rated operating voltage U_e [V]: 690
 Rated insulation voltage U_i [V]: 690
 Rated impulse withstand voltage U_{imp} [kV]: 4
 Rated thermal current I_{th} [A]: 16
 Rated thermal current I_{the} [A]: 16
 Frequency [Hz]: 50/60
 Rated operating current: AC 15 – DC 13

GM756/FR

GM756/US

GM756/SW



GM756/UK

GM756/CH



GM754

IP65  Magnets on the bottom by request

DESCRIPTION	SCHEME
Emergency stop EN ISO 13850 Ø 40 push-pull with:	
1 Up push button - 2NO - 1NC 	
1 Down push button - 2NO - 1NC 	
1 Alarm push button - 1NO 	
1 Common push button - 2NO 	
1 Cam switch 1-2 90° switching - 2NO + 2NC	
1 Knob selector 1-O-2 1NO+1NO 	
1 Red led light	 AC/DC 24V

CAM SWITCHES

Rated operating voltage U_e [V]: 690
 Rated insulation voltage U_i [V]: 690
 Rated impulse withstand voltage U_{imp} [kV]: 4
 Rated thermal current I_{th} [A]: 20
 Rated thermal current in enclosure I_{the} [A]: 16
 Frequency [Hz]: 50/60

CONTACT BLOCKS

Rated operating voltage U_e [V]: 690
 Rated insulation voltage U_i [V]: 690
 Rated impulse withstand voltage U_{imp} [kV]: 4
 Rated thermal current I_{th} [A]: 16
 Rated thermal current I_{the} [A]: 16
 Frequency [Hz]: 50/60
 Rated operating current: AC 15 – DC 13





PIT BOTTOM, RECALL DRIVE CONTROL UNITS AND CAR TOP INSPECTION BOXES - GM Series

GM412

IP54


DESCRIPTION

SCHEME


Emergency stop EN ISO 13850
Ø 40 twist to release with:



1 Up push button - 2NO - 1NC



1 Down push button - 2NO - 1NC



1 Alarm push button - 1NO



1 Common push button - 2NO



1 Cam switch 1-2
90° switching - 3NO + 3NC



1 Schuko socket outlet 16A



1 Cenelec socket outlet



1 USA socket outlet



1 Swiss socket outlet



1 UK standard socket outlet



1 Australia-China socket outlet



CAM SWITCHES

Rated operating voltage U_e [V]: 690
Rated insulation voltage U_i [V]: 690
Rated impulse withstand voltage U_{imp} [kV]: 4
Rated thermal current I_{th} [A]: 20
Rated thermal current in enclosure I_{the} [A]: 16
Frequency [Hz]: 50/60

CONTACT BLOCKS

Rated operating voltage U_e [V]: 690
Rated insulation voltage U_i [V]: 690
Rated impulse withstand voltage U_{imp} [kV]: 4
Rated thermal current I_{th} [A]: 16
Rated thermal current I_{the} [A]: 16
Frequency [Hz]: 50/60
Rated operating current: AC 15 – DC 13

GM412/FR

GM412/US

GM412/SW

GM412/UK

GM412/CH

GM822

IP54


DESCRIPTION

SCHEME

Emergency stop EN ISO 13850
Ø 30 twist to release with:




1 Up push button - 2NO - 1NC



1 Down push button - 2NO - 1NC




1 Alarm push button - 1NO




1 Common push button - 2NO



1 White LED light



1 Cam switch 1-2
90° switching - 3NO + 3NC



CAM SWITCHES

Rated operating voltage U_e [V]: 690
Rated insulation voltage U_i [V]: 690
Rated impulse withstand voltage U_{imp} [kV]: 4
Rated thermal current I_{th} [A]: 20
Rated thermal current in enclosure I_{the} [A]: 16
Frequency [Hz]: 50/60

CONTACT BLOCKS

Rated operating voltage U_e [V]: 690
Rated insulation voltage U_i [V]: 690
Rated impulse withstand voltage U_{imp} [kV]: 4
Rated thermal current I_{th} [A]: 16
Rated thermal current I_{the} [A]: 16
Frequency [Hz]: 50/60
Rated operating current: AC 15 – DC 13

1 Schuko socket outlet 16A



1 Cenelec socket outlet



1 USA socket outlet



1 Swiss socket outlet



1 UK standard socket outlet



1 Australia-China socket outlet



GM822/FR

GM822/US

GM822/SW

GM822/UK

GM822/CH



GM321

IP54

DESCRIPTION

Emergency stop EN ISO 13850
Ø 40 push-pull with:

1 Up push button - 2NO

1 Down push button - 2NO

1 Alarm/Light dual push button
1NO+1NO

1 Blue push button - 1NO

1 Cam switch 1-2
90° switching - 2NO + 4NC

2 Knob selector 1-0-2 1NO+1NO

1 Schuko socket outlet 16A

1 Cenelec socket outlet

1 USA socket outlet

1 Swiss socket outlet

1 UK standard socket outlet

1 Australia-China socket outlet

SCHEME

CAM SWITCHES

Rated operating voltage U_e [V]: 690

Rated insulation voltage U_i [V]: 690

Rated impulse withstand voltage U_{imp} [kV]: 4

Rated thermal current I_{th} [A]: 20

Rated thermal current in enclosure I_{the} [A]: 16

Frequency [Hz]: 50/60

CONTACT BLOCKS

Rated operating voltage U_e [V]: 690

Rated insulation voltage U_i [V]: 690

Rated impulse withstand voltage U_{imp} [kV]: 4

Rated thermal current I_{th} [A]: 16

Rated thermal current I_{the} [A]: 16

Frequency [Hz]: 50/60

Rated operating current: AC 15 – DC 13

GM321/FR
GM321/US
GM321/SW
GM321/UK
GM321/CH


GM520

IP55

DESCRIPTION

Emergency stop EN ISO 13850
Ø 30 twist to release with:

1 Up push button - 1NO

1 Down push button - 1NO

1 Plug

1 Common push button - 1NO

1 Cam switch 1-2
90° switching - 1NO + 1NC

1 Schuko socket outlet 16A

1 Cenelec socket outlet

1 USA socket outlet

1 Swiss socket outlet

1 UK standard socket outlet

1 Australia-China socket outlet

SCHEME

CAM SWITCHES

Rated operating voltage U_e [V]: 690

Rated insulation voltage U_i [V]: 690

Rated impulse withstand voltage U_{imp} [kV]: 4

Rated thermal current I_{th} [A]: 20

Rated thermal current in enclosure I_{the} [A]: 16

Frequency [Hz]: 50/60

CONTACT BLOCKS

Rated operating voltage U_e [V]: 690

Rated insulation voltage U_i [V]: 690

Rated impulse withstand voltage U_{imp} [kV]: 4

Rated thermal current I_{th} [A]: 16

Rated thermal current I_{the} [A]: 16

Rated operating current: AC 15 – DC 13

Frequency [Hz]: 50/60

GM520/FR
GM520/US
GM520/SW
GM520/UK
GM520/CH




GMS03

IP54 

DESCRIPTION

Emergency stop
EN ISO 13850

Ø 40 twist to release with:


SCHEME



1 Up push button - 1NO - 1NC



1 Down push button - 1NO - 1NC



1 Green push button - 1NO




1 Blue push button - 1NO



1 Black push button - 1NO



1 Cam switch 1-2
90° switching - 1NO + 1NC



1 Schuko socket outlet 16A



1 USA socket outlet



CAM SWITCHES

Rated operating voltage U_e [V]: 690

Rated insulation voltage U_i [V]: 690

Rated impulse withstand voltage U_{imp} [kV]: 4

Rated thermal current I_{th} [A]: 20

Rated thermal current in enclosure I_{the} [A]: 16

Frequency [Hz]: 50/60

CONTACT BLOCKS

Rated operating voltage U_e [V]: 690

Rated insulation voltage U_i [V]: 690

Rated impulse withstand voltage U_{imp} [kV]: 4

Rated thermal current I_{th} [A]: 16

Rated thermal current I_{the} [A]: 16

Frequency [Hz]: 50/60

Rated operating current: AC 15 – DC 13

GM004

IP65 




DESCRIPTION


Emergency stop
EN ISO 13850

Ø 40 push-pull with:


SCHEME




1 multi-function button
Yellow - Green 2NO



1 multi-function button
Up - Down 2NO



1 Cam switch 1-2
90° switching 1NO + 1NC



CAM SWITCHES

Rated operating voltage U_e [V]: 690

Rated insulation voltage U_i [V]: 690

Rated impulse withstand voltage U_{imp} [kV]: 4

Rated thermal current I_{th} [A]: 20

Rated thermal current in enclosure I_{the} [A]: 16

Frequency [Hz]: 50/60

CONTACT BLOCKS

Rated operating voltage U_e [V]: 690

Rated insulation voltage U_i [V]: 690

Rated impulse withstand voltage U_{imp} [kV]: 4

Rated thermal current I_{th} [A]: 16

Rated thermal current I_{the} [A]: 16




Frequency [Hz]: 50/60

Rated operating current: AC 15 – DC 13

SPECIAL GM Series for SCENIC LIFT

GM412Black

IP54 

DESCRIPTION	SCHEME
Emergency stop EN ISO 13850 Ø 40 push-pull with:	
1 Up push button - 2NO - 1NC 	
1 Down push button - 2NO - 1NC 	
1 Alarm push button - 1NO 	
1 Common push button - 2NO 	
1 Cam switch 1-2 90° switching - 3NO + 3NC 	
1 Schuko socket outlet 16A 	
1 Cenelec socket outlet 	
1 USA socket outlet 	
1 Swiss socket outlet 	
1 UK standard socket outlet 	
1 Australia-China socket outlet 	

CAM SWITCHES

Rated operating voltage U_e [V]: 690
 Rated insulation voltage U_i [V]: 690
 Rated impulse withstand voltage U_{imp} [kV]: 4
 Rated thermal current I_{th} [A]: 20
 Rated thermal current in enclosure I_{the} [A]: 16
 Frequency [Hz]: 50/60

CONTACT BLOCKS

Rated operating voltage U_e [V]: 690
 Rated insulation voltage U_i [V]: 690
 Rated impulse withstand voltage U_{imp} [kV]: 4
 Rated thermal current I_{th} [A]: 16
 Rated thermal current I_{the} [A]: 16
 Frequency [Hz]: 50/60
 Rated operating current: AC 15 – DC 13

GM412Black/FR

GM412Black/US

GM412Black/SW


GM412Black/UK

GM412Black/CH



GM660Black

IP54 *Magnets on the bottom by request*

DESCRIPTION	SCHEME
Emergency stop EN ISO 13850 Ø 40 twist to release with:	
1 Up push button - 2NO 	
1 Down push button - 2NO 	
1 Common push button - 2NO 	
1 Cam switch 1-2 90° switching - 3NO + 3NC 	
1 Schuko socket outlet 16A 	
1 Cenelec socket outlet 	
1 USA socket outlet 	
1 Swiss socket outlet 	
1 UK standard socket outlet 	
1 Australia-China socket outlet 	

CAM SWITCHES

Rated operating voltage U_e [V]: 690
 Rated insulation voltage U_i [V]: 690
 Rated impulse withstand voltage U_{imp} [kV]: 4
 Rated thermal current I_{th} [A]: 20
 Rated thermal current in enclosure I_{the} [A]: 16
 Frequency [Hz]: 50/60

CONTACT BLOCKS

Rated operating voltage U_e [V]: 690
 Rated insulation voltage U_i [V]: 690
 Rated impulse withstand voltage U_{imp} [kV]: 4
 Rated thermal current I_{th} [A]: 16
 Rated thermal current I_{the} [A]: 16
 Frequency [Hz]: 50/60
 Rated operating current: AC 15 – DC 13

GM660Black/FR

GM660Black/US

GM660Black/SW

GM660Black/UK

GM660Black/CH





GIOVENZANA INTERNATIONAL B.V.

1077 XX Amsterdam, The Netherlands
WTC Strawinskylaan 1105
Ph. +31(0) 20.4413576 - Fax +31(0) 20.4413456
e-mail: giovenzana@giovenzana.com

G.M.K. K.f.t.

1068 Budapest, Hungary
Rippl Ronai ut. 13
Ph. +36.37.572575 - Fax +36.37.572570
e-mail: gmk@giovenzana.com

G.T.R. LCC

Moscow, Russian Federation
Ulitsa Radio 24, Yauza Tower 4th floor
Ph. +7.495.6991296 / 6503959 - Fax +7.495.6991520
e-mail: gtr@giovenzana.com

GIOVENZANA CONTROLS INDIA Pvt. Ltd.

Mumbai
Ph. +91.22.42640071
e-mail: ggindia@giovenzana.com

Branch

DUBAI U.A.E. P.O. Box 262146 - J.A.F.Z.A. 15, Jebel Ali Free
Zone
Ph. +971.4.8870788 - Fax +971.4.8870787
e-mail: uae@giovenzana.com